



ecodek® 40mm x 48mm Low Profile Bearer

The 40mm x 48mm profile is intended for use as a bearer profile to support various composite and timber decking products and must be installed to the following specification:

- Bearer must be supported at a maximum of 500mm between centres for most applications such as residential decks, boardwalks etc.
- The bearer can be supported on rubber packers or adjustable pedestals (available from us).
- Must be installed with the 48mm dimension as the upright.
- Each bearer must be supported in at least 3 places.
- Bearer must not overhang its support by more than 50mm.
- Must be pre-drilled to the same depth as the decking screw with an appropriately sized drill bit (for most

composite decking screws we recommend a 3.5mm drill bit). This is very important to ensure that the screws do not overheat (and therefore weaken) whilst being screwed in.

- Bearer is designed to take live loads only. Any static loads must be positioned over the bearer supports.
- Maximum loadings: UDL of 9.6kN/m² live load (i.e. non-static). Point load of 4.5kN live load mid span to BS 1195:1998
- N.B. Screwing through the product is not best practice, but if absolutely necessary then the max screw size allowable is 4mm (No8) and the hole must be pre-drilled with a 3.5 or 4mm drill bit.

Do not screw within 20mm of the edge of the profile in case of splitting. We advise using joist hangers wherever possible to minimize through-holes in supports.

